



# MAXAM

# MS203

E2/G2/L2

Non-directional pattern designed to maximize traction in soft underfoot conditions. Ideal for use on graders, loaders and earthmovers.

- All-steel radial tire construction maximizes traction and flotation
- Wear and cut resistant tread compound
- Self-cleaning tread design

Applications:



| Size     | Rating | Type | Rim       | O.D.     | S.W.     | T.D.        | Infl. P.   | L.C.C.<br>(lbs/kg) | Infl. P.   | L.C.C.<br>(lbs/kg) | L.I.       |
|----------|--------|------|-----------|----------|----------|-------------|------------|--------------------|------------|--------------------|------------|
|          |        |      |           | in<br>mm | in<br>mm | 32nds<br>mm | psi<br>KPa | 5 mph<br>10 kph    | psi<br>KPa | 30 mph<br>50 kph   |            |
| 14.00R24 | ★      | TL   | 10.00VA   | 54.0     | 14.8     | 32          | 80         | 15200              | 69         | 9100               | 175A2/157B |
|          |        |      |           | 1371     | 376      | 25          | 550        | 6900               | 475        | 4125               |            |
| 17.5R25  | ★      | TL   | 14.00/1.5 | 53.1     | 17.5     | 35          | 73         | 15700              | 54         | 9100               | 176A2/157B |
|          |        |      |           | 1348     | 445      | 28          | 500        | 7100               | 375        | 4125               |            |
| 20.5R25  | ★      | TL   | 17.00/2.0 | 58.5     | 20.5     | 39          | 73         | 20900              | 54         | 12300              | 186A2/168B |
|          |        |      |           | 1486     | 521      | 31          | 500        | 9500               | 375        | 5600               |            |
| 23.5R25  | ★      | TL   | 19.50/2.5 | 63.1     | 23.9     | 43          | 73         | 26800              | 54         | 15700              | 195A2/176B |
|          |        |      |           | 1603     | 607      | 34          | 500        | 12150              | 375        | 7100               |            |

